



Datasheet

Circularly Polarized Active GPS Embedded Ceramic Patch Antenna

Model: AIGC054

PN: M01-0300260R0A

Description:

Active B1/L1/E1 Band BDS/GPS/Galileo Antenna for Meshtastic Handle

Operating Frequency: 1550 -1580 MHz

Features:

Ceramic Patch Element

Low Axial Ratio

Dimensions: 15 x 15 x 4 mm

PCB Board: 15 x 15 x 0.6 mm

Ground Plane Dependent

RoHS & Reach Compliant



ABOOSTY



Table of Contents

FEATURES & BENEFITS	1
ANTENNA IMAGE	1
ORDER INFORMATION	1
APPLICATIONS	1
GNSS FREQUENCY BANDS	2
REFERENCE GUIDE	3
ELECTRICAL PERFORMANCE	4
S21 (dB) and S22	4
Passive Gain (dBi) and Total Efficiency (%)	5
2D and 3D Radiation Patterns (1550-1580 MHz)	7
MECHANICAL DIMENSIONS	8

www.aboosty.com

The materials provided herein, which are intended for illustration purposes only, are believed to be reliable and correct. However, no responsibility is further assumed for inaccuracies or incompleteness, and all such information shall be entirely at the user's risk. All information is subject to change without prior notice.

Copyright © 2025 ShenZhen MyAntenna RF Technology Co., Ltd. All Rights Reserved.

Abosty™ is owned by Shenzhen MyAntenna RF Technology Co., Ltd. (often abbreviated as MyAntenna).






FEATURES & BENEFITS

- 15x15x4mm Embedded Ceramic Patch Element
- Miniaturized, Multi-system Compatible
- Low Axial Ratio
- Ground Plane Dependent
- RoHS & Reach Compliant
- Covering Bands: GPS (L1) / Galileo (E1) / BeiDou (B1)

APPLICATIONS

- Hand-held/Portable Devices
- Asset and Fleet Tracking
- Scientific Instrumentations
- Oil, Gas, and Mining Industries
- M2M Applications
- Precision Agriculture

ANTENNA IMAGE



ORDER INFORMATION


Product Name	Circularly Polarized Active GPS Embedded Ceramic Patch Antenna
Model	AIGC054
Part Number	M01-0300260R0A
Dimensions	15 x 15 x 4 mm (PCB Board: 15 x 15 x 0.6 mm)
Weight	5.8 g
Mounting	Internal/Embedded/Adhesive mount
Cable Length	120mm
Cable and Connector	IPEX 1, RF 1.13 (Ø 1.13 mm) coaxial cable, customizable.



GNSS FREQUENCY BANDS

GNSS Frequency Bands Covered					
GPS	L1	L2	L5		
	●	○	○		
GLONASS	G1	G2	G3		
	○	○	○		
Galileo	E1	E5a	E5b	E6	
	●	○	○	○	
Bei Dou	B1I	B1C	B2a	B2b	B3
	●	●	○	○	○
QZSS (Regional)	L1	L2C	L5	L6	
	●	○	○	○	
IRNSS(Regional)	L5				
	○				
SBAS	L1/E1/B1	L5/B2a/E5a	G1	G2	G3
	●	○	○	○	○

*SBAS systems: WASS(L1/L5), EGNOS(E1/E5a), SDCM(G1/G2/G3), SNAS(B1,B2a), GAGAN(L1/L5), QZSS(L1/L5), KAZZ(L1/L5).





REFERENCE GUIDE

Antenna				
Frequency	1550-1580 MHz			
Technical Features (MHz)	BeiDou	Galileo	GPS	GLONASS
	1561 ± 2	1575.42 ± 2	1575.42 ± 2	/
Frequency Bands	B1 Band	E1 Band	L1 Band	G1 Band
VSWR	<1.8			
Peak Gain (dBi)	-0.55			
Efficiency (%)	51.25			
Axial Ratio (dB)	<3			
Noise Figure (dB)	<1.8			
Polarization	RHCP			
Radiation Pattern	Directional			
Input Impedance	50 Ω			
LNA				
Frequency Bands	B1 Band	E1 Band	L1 Band	G1 Band
LNA Gain (dB)	17.9	19.1	19.1	17.6
Input Voltage	3.3 ± 0.3 V			
Current Consumption @3.0V	8 ± 1 mA (@3.3 V)			
Environmental				
Operating Temperature	-40°C to +85°C			
Storage Temperature	-40°C to +90°C			
Relative Humidity	Non-condensing 65°C 95% RH			
Vibration	Wave Form: Random Vibration			
	Test Time: 30min/Axis			
	Direction: X, Y, Z Axis			
	PSD Break Points for 9.8 RMS (m/s²)	Frequency (Hz)	50	300
		Acceleration ((m/s²)²/Hz)	0.38416	0.38416
RoHS Compliant	Yes			
All data were measured with a 120-mm long RF 1.13 cable. Application data might vary.				




ELECTRICAL PERFORMANCE

⦿ Note

All data displayed in "ELECTRICAL PERFORMANCE" were measured with a 120-mm-long RF 1.13 cable.


S21 (dB) and S22



(Note: Data were tested with a 120 mm of RF 1.13 cable.)



Passive Gain (dBi) and Total Efficiency (%)





(Note: Data were tested with a 120 mm of RF 1.13 cable.)



Antenna Data		
Freq (MHz)	Gain (dBi)	Efficiency (%)
1505	-13.13	4.14
1510	-12.21	4.83
1515	-11.68	5.49
1520	-10.74	6.69
1525	-9.98	8.23
1530	-8.94	10.25
1535	-8.03	13.22
1540	-6.36	18.13
1545	-5.03	24.37
1550	-3.22	35.12
1555	-1.64	47.28
1560	-0.65	51.25
1565	-0.36	43.25
1570	-0.54	40.91
1575	-2.43	36.71
1580	-4.4	26.89
1585	-6.07	19.66
1590	-7.43	14.62
1595	-8.72	11.11
1600	-9.72	9.23
1605	-10.75	7.24

2D and 3D Radiation Patterns (1550-1580 MHz)






3D at 1575 MHz, Gain=-2.43 dBi



MECHANICAL DIMENSIONS



ABOOSTY WELCOME ALL ANTENNA OEM/ODM PROJECTS

Why Choose ABOOSTY



10+ years in antenna R&D, production, and OEM/ODM



MES system supported factory; 50M+ units annual output capacity



Factory directly competitive price



Quick price and lead time estimate



Innovative and patented design solutions




Professional team support & prompt reply within 24h

What We Provide


OEM/ODM Services	Light Customization	Deep Customization
	• Logo • Packaging • Cables & Connectors	• In-depth tailoring for specific applications • Functional enhancements • Environmental adaptations • Vertical certifications • ...

Custom Process

Light Customization Process



Deep Customization Process



Note: You can let us handle the PCB prototyping or do it yourself. Choosing self-prototyping may add 2 to 5 weeks to the timeline.

Boost Your Signal
with Our Antennas

ABOOSTY

A Globally Leading Manufacturer and Supplier of
Multi-band Combination Antennas

Contact us:

 support@aboosty.com

 +86-13924678201

Find us (Global):

 www.aboosty.com

Search to follow us or to get technical support.



@Aboosty



Aboosty Antenna



Or click here to reach us directly.



 国内官网: www.aboosty.cn

